

BCI Maximum Overall Dimensions (Inches)			Reserve Capacity	Cranking Performance		WBI Part Number	BCI Group Size
ابعاء به اینچ				ظرفیت ذخیره	تست باتری		
Height	Width	Length	@80F	@32F	@0F		
ارتفاع	عرض	طول		معمولی	سرد		
8.313	6.875	9.5	80	490	390	X22F	22F
8.313	6.875	9.5	80	490	390	C22F	
8.938	5.5	9.438	65	440	350	C22NF	22NF
8.875	6.812	10.25	125	825	700	24-7	24
8.875	6.812	10.25	100	750	600	X24	
8.875	6.812	10.25	102	715	580	C24H	
8.875	6.812	10.25	90	660	530	C24	
8.875	6.812	10.25	70	525	420	A24	
8.875	6.812	10.25	155	875	700	24F-7	
8.875	6.812	10.25	100	750	600	X24F	24F
8.875	6.812	10.25	102	715	580	C24FH	
8.875	6.812	10.25	90	660	530	C24F	
8.875	6.812	10.25	70	525	420	A24F	
8.875	6.875	9.063	100	710	570	C25	25
8.063	6.812	8.188	85	625	500	X26	26
8.063	6.812	8.188	85	625	500	C26	
8.063	6.812	8.188	85	625	500	A26	
8.875	6.812	12.063	125	875	700	27HD	27
8.875	6.812	12.063	100	700	560	X27	
8.875	6.812	12.5	100	700	560	X27F	27F
8.938	5.5	13	100	525	420	A29NF	29NF
7.812	6.812	10.25	110	720	575	C34	34
8.875	6.875	9.063	100	710	570	C35	35
7.5	4.688	13	69	405	330	A53	53
8.375	6.063	8.625	75	560	450	X55	55
8.375	6.063	8.625	75	560	450	C55	
7	7.25	9.438	90	720	575	X58	58
7	7.25	9.438	80	575	460	C58	
7	7.25	9.438	80	575	460	C58R	58R
8.75	6.25	13	127	480	440	A60	60
8.875	6.438	8.938	80	575	460	X62	62
8.875	6.438	8.938	80	575	460	C62	
8.875	6.438	11.688	110	750	600	X64	64
7.563	7.5	11.375	150	1060	850	C65	65
7.563	7.5	11.375	150	1060	850	A65	
7.75	7.063	8.188	90	625	500	X70	70
7.75	7.063	8.188	90	625	500	C70	

7.75	7.063	8.188	90	625	500	A70	
8.75	7.25	10.25	155	1015	825	74-825	74
8.75	7.25	10.25	??105	860	690	X74	
8.75	7.25	10.25	102	715	580	C74H	
8.75	7.25	10.25	95	625	500	C74	
8.75	7.25	10.25	75	525	420	A74	
7.75	7.063	9.063	105	720	575	X75	75
7.75	7.063	9.063	105	720	575	C75	
7.75	7.063	10.25	130	690	550	C78	78
6.875	6.875	8.25	40	310	245	239	39
6.875	6.875	11.563	110	760	610	X41	41
6.812	6.812	9.563	75	530	425	X42	42
8.938	5.5	9.438	70	490	390	X45	45
8.875	6.812	10.25	80	625	510	C46	46
7	6.875	9.5	100	575	460	C47	47
7.063	6.875	10.938	70	690	550	C48	48
6.938	6.875	13.938	90	940	750	C49	49
8.875	5.063	9.375	70	540	435	C51	51
8.875	5.063	9.375	70	545	435	C51R	51R